

BODACIOUS

HIGH PRESSURE, NON-MELT RED GREASE



DESCRIPTION

BODACIOUS is a USDA authorized high temperature, non-melting, inorganic red grease which will withstand temperatures up to 500°F. It sprays out as a thick liquid which transforms into a grease in minutes. This product penetrates, lubricates and prevents rust on all metal parts. Containing a high pressure additive, it reduces wear and extends operating life of all parts and machinery. It prevents seizing and loosens frozen parts. It contains no fluorinated solvents making it more environmentally friendly than its traditional counterparts. Due to VOC regulations, not available for sale in California and Utah.

APPLICATIONS

For use on machinery, conveyors, chains, cables, gears, winches, tools and rollers. Areas of use include farms, oil rigs and refineries, bottling plants, dairies, paper mills, cotton gins, air conditioning, industrial plants, textile plants, lumber mills, cement plants and automotive/motorcycle/marine repair.

FEATURES & BENEFITS

- Prolongs life of metal parts
- Contains corrosion and rust inhibitors
- High shock and impact resistance
- Exceptional adhesive cohesive and anti-wear properties

SPECIFICATIONS

FORM: Solvent Based Aerosol
ODOR: Petroleum
COLOR: Red
DETERGENCY: None
TOXICITY: 25 ppm OSHA TLV
WETTING ABILITY: Saturates
STORAGE STABILITY: 1 Year +
COLD STABILITY: 0°F
PHOSPHATES: None

FLASH POINT: N/A
FLAME EXTENSION: 20"
SOLUBILITY IN WATER: 0%
SPECIFIC GRAVITY: 0.93
% VOLATILE BY VOLUME: 48.8%
pH: N/A
PROPELLANT: Hydrocarbon
EVAPORATION RATE: N/A
BIODEGRADABILITY: No

LABEL INFORMATION

BODACIOUS NON-MELT GREASE SPRAY

This product is a multi-purpose lubricant penetrant that seeks hard to reach areas for tough, long lasting grease protection. Product sprays out as a thick liquid which transforms into a grease in one to two minutes. Cured lubricant withstands heat to 500°F, moisture, acids, high pressure and is highly rust resistant. Use on chains, winches, conveyors, gears, cables, tools, hinges, bushings, pins, levers and rollers. A high pressure additive reduces wear and prolongs operational life of all machinery. Temperatures above 375°F may require periodic reapplication.

DIRECTIONS FOR USE: Shake well before using. Remove protective cap. Point opening in spray tip towards area to be sprayed. For hard to reach areas insert red extender tube in hole in tip. Apply a light coat by spraying in quick, short bursts. Work part to distribute product evenly over entire surface. Spray as necessary to insure full coverage.


DANGER: Extremely Flammable Aerosol. Contains gas under pressure; may explode if heated. Causes skin and eye irritation. Suspected of causing cancer. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways.

Keep away from heat, sparks, open flames, and hot surfaces. –No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Wash hands thoroughly after handling. Wear protective gloves. Avoid breathing fumes, vapors, and spray. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. If swallowed: Immediately call a poison center or doctor. Do NOT induce vomiting. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. If exposed or concerned: Get medical advice or attention. Use only outdoors or in a well-ventilated area. Store locked up. Dispose of contents and container in accordance with local, state, and national regulations.

WARNING: This product contains a chemical(s) known to the State of California to cause cancer.

CONTAINS (CAS#): Heptane (142-82-5), Heavy Naphthenic Petroleum Distillate (64742-52-5), Propane/n-Butane (68476-86-8), Tetrachloroethylene (127-18-4), Organophilic Clay (N/A).

HEALTH	2
FLAMMABILITY	3
REACTIVITY	0
PERSONAL	B



PACKAGING INFORMATION

5720: 12 – 16 oz. cans per case, 12 oz. net weight
 5730: 12 – 20 oz. cans per case, 15 oz. net weight (Private Label Only)