



EZ LUBE

FOOD GRADE WHITE GREASE

DESCRIPTION

A multi-purpose, high purity food grade lubricant that provides long lasting grease protection. Withstands heat to 500°F. Temperatures above 400°F may require periodic reapplication. NSF rated H1.

APPLICATIONS

For use by bakeries, bottlers, breweries, canneries, dairies, egg processors, meat and poultry processors, pharmaceutical manufacturers and food processing and packaging plants.

FEATURES & BENEFITS

- Lubricates
- Resists extreme pressure, corrosion & water washout
- Temperature range of -40° – 500°F
- Reduces friction & wear
- Resists throw-off
- Calcium sulfonate based

SPECIFICATIONS

COLOR: White
THICKENER: Calcium Sulfonate
NLGI GRADE: 2
PENETRATION: 265–295
DROPPING POINT: 550°F
TEMPERATURE RANGE: -40°F – 500°F

TIMKEN OK LOAD: 60 lbs.
BASE OIL: Mineral Oil
VISCOSITY N/A
NSF RATING: H1
FOUR BALL EP LOAD: 620 kg

LABEL INFORMATION

EZ LUBE FOOD GRADE WHITE GREASE

A multi-purpose, high purity food grade lubricant that provides long lasting grease protection. Withstands heat to 500°F. Temperatures above 400°F may require periodic reapplication.


FOR USE BY: Bakeries, Bottlers, Breweries, Canneries, Dairies, Egg Processors, Meat and Poultry Processors, Pharmaceutical Manufacturers and Food Processing and Packaging Plants.

DIRECTIONS FOR USE: Pump in new grease until old grease comes out. Remove old grease if possible. For ball type grease fittings, fill until old grease comes out. Clean exposed areas with degreaser to remove old grease. Pump in new grease.

CAUTION: Keep out of reach of children. May cause irritation to eyes. Prolonged contact with skin may cause irritation. If ingested, may cause nausea, vomiting, and diarrhea. For eye contact, flush with water, see physician if oily film persists. For skin, wash with soap and water. For ingestion of more than 8 ounces contact physician.

CONTAINS (CAS#): Mineral Oil (8042-47-5), Calcium Sulfonate Complex (N/A).

HEALTH	0
FLAMMABILITY	1
REACTIVITY	0
PERSONAL	A



Nonfood Compounds
H1
150708

PACKAGING INFORMATION

Available in 14 oz. cartridges (10/case), 35 lb. pails and 120 and 400 lb. drums.